

Dryrox

Watch dryer (before condensation test)

Datasheet, 30.03.2023, V2.0

 Engineered and made in Switzerland

The Dryrox device is a machine allowing to dry a batch of watches by compressed air during a configurable time.

Machine functions

- Drying by compressed air
- 2 adjustable nozzles,
 - Upper (from 0,5 to 6 bar)
 - Lower (from 0 to 4 bar)
- Clockwise and counterclockwise rotation
- Average cycle time 60 seconds
- Viewing window
- Color touch-screen
- RS-232 output

Software functions

- Intuitive menus in 5 languages
- Many adjustable parameters
- Simple and intuitive programming
- Programmable and memorable cycles
- Cycle starts automatically at the closing of the cover

Technical specifications

Supply voltage :	110-230 V / 50-60 Hz
(External power supply, transformer 24 VDC / 1,25 A / 30 W)	
Power :	190 W
Inlet pressure :	7,5 bar
Airflow :	200 l / min
Rotation frequency :	1 to 12 tr / min
Ø Borehole mini :	18 mm
Ø Tray maxi :	256 mm
Capacity :	Up to 20 watches (1 tray)
Weight :	13,5 kg
Dimensions closed device (l/d/h) :	360 x 425 x 235 mm
Dimensions open device (l/d/h) :	360 x 425 x 610 mm

